

HI-TEMP RESTORATION PRODUCTS

THE ULTIMATE IN RESTORATION SOLUTIONS USING TODAY'S TECHNOLOGY

Pyro-Putty®

These high temperature ceramic and metal-filled pastes are ideal for repairing pinholes, warps and cracks in manifolds, headers, exhaust pipes, mufflers, and more. Pyro-Putty metal repair compounds bond tenaciously to cast aluminum, cast iron, steel, and stainless steel, and are easy to apply, cure, machine and clean up.

Aremco-Bond[™]

These 400 °F high performance, structural epoxies are ideal for repairing cast aluminum, cast iron, steel and stainless steel components. Aremco-Bond[™] is supplied in ready-to-use 1-to-1 cartridges for precise metering and mixing of the epoxy. Curing takes place at room temperature in 24 hours. Shear strengths in excess of 3000 psi are achieved.

Corr-Paint™

These heat resistant coatings were originally developed to protect high temperature industrial process equipment from oxidation and corrosion. They are specially formulated using a water-dispersed, inorganic binder combined with corrosion resistant metallic and metal-oxide fillers and pigments that are stable to 1500 °F. Corr-Paint is ideal for coating cylinder heads, manifolds, headers, stoves, etc... Available in aluminum, black and stainless steel colors.

Pyro-Seal[™]

The ultimate engine block and cylinder head sealer. This single-part, water-based, air-set material produces a tough, flexible film that seals fine cracks, pinholes and porosity in cast iron and cast aluminum. Resists boiling anti-freeze and gets stronger with heat!

Stock #	Description	Size
1000-K	Pyro-Putty [®] Kit 1400 °F for Cast Aluminum Repair	8 oz Powder 4 oz Liquid
2400-K	Pyro-Putty [®] Kit 2000 °F for Cast Iron, Steel, Stainless Steel	8 oz Paste 4 oz Thinner
568-K	Aremco-Bond™ Kit 400 °F for Aluminum Repair	568-C 50ml Cartridge x 1 9850 Plunger x 1 9910 Nozzle x 2
657-K	Aremco-Bond™ Kit 400 °F for Cast Iron, Steel, Stainless Steel	657-C 50ml Cartridge x 1 9850 Plunger x 1 9910 Nozzle x 2
CP3015-AL	Corr-Paint™ Aluminum Pigmented for 1500 °F Service	1 Pint 1 Quart
CP3015-BL	Corr-Paint™ Black Pigmented for 1500 °F Service	1 Pint 1 Quart
CP3015-SS	Corr-Paint™ Stainless Steel Filled for 1500 °F Service	1 Pint 1 Quart
PS6000	Pyro-Seal™ Head and Block Sealer	Quart Gallon

IT'S EASY TO ORDER. JUST GIVE US A CALL!

Call Monday through Friday between 8:30 a.m. and 5:30 p.m. EST. for technical assistance and to place orders. All orders are processed within 24 hours.



VISA

AREMCO PRODUCTS, INC. P.O.BOX 517 - 707-B EXECUTIVE BOULEVARD VALLEY COTTAGE, NY 10989 TEL: (845) 268-0039 • FAX: (845) 268-0041 www.aremco.com • aremco@aremco.com



Corr-Paint[™] CP3015-AL aluminum-rich, water-dispersible paint is used to coat heat shield and spark plugs on aircraft engine manifold.



Pyro-Putty[®] 2400 is used here to repair a cracked exhaust manifold, saving time and money!

